PATENT ABSTRACTS OF JAPAN

(11)Publication number:

11-215871

(43)Date of publication of application: 06.08.1999

(51)Int.CI.

H02P 3/12

H02P 7/06 H02P 7/285

(21)Application number: 10-013618

(71)Applicant: MATSUSHITA ELECTRIC WORKS LTD

(22)Date of filing:

27.01.1998 (72)Invento

(72)Inventor: MATSUMOTO TATSUHIKO

NAGAHAMA HIDEO OHASHI TOSHIHARU KUBOTA ATSUMASA


SHIMIZU HIDEKI

(54) MOTOR CONTROLLER

(57) Abstract:

PROBLEM TO BE SOLVED: To immediately stop the rotation of a DC motor when abnormality is detected, and besides, lighten the voltage stress or current stress of a MOSFET.

SOLUTION: A switch circuit 1 is equipped with a MOSFET Q1 connected in series to a DC motor M, and a MOSFET Q2 connected in parallel with the DC motor M. The series circuit of the DC motor M and the MOSFET Q1 is connected to a battery B at low voltage. When the MOSFET Q1 is turned on by a control signal generating circuit 22, the DC motor M is driven. Moreover, when the load of the DC motor M becomes large, and an overload signal is generated, the control signal generating circuit 22 turns off the MOSFET Q1 and turns on the MOSFET Q2, and lets the regenerated current of the DC motor M flow to the MOSFET Q2. In short, the DC motor M is stopped in a short time by letting the regenerated current flow to the DC motor M.



LEGAL STATUS

[Date of request for examination]

09.07.2001

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of

rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office